


FEATURES

- | For up to 12.302 liters of total sprinkler pipe capacity
- | UL 508A listed Industrial Control Panel
- | CE compliant
- | Dual-Bed PSA technology
- | BlastOff™ I - Leak Detection System
- | BlastOff II - Auto Air Bypass Alarm
- | Requires separate feed air compressor
- | Integrated Air Dryer and N₂ receiver tank
- | Touchscreen/HMI with Smart-Trak™ technology
- | Optional BlastOff III – Early Warning System
- | Optional BlastOff IV – Onboard Purity Alarm

UNIT DETAILS

N ₂ Blast FPS-3250	
Part Number	
N ₂ Generation System	FPS-03250
AutoPurge System [®]	A03-APS2
Air Compressor Package (3HP, 7.5HP, 10HP)	STS-NF-C- (3-L, 7-L, 10-L)
Dimensions	
A (Width)	660,4mm
B (Depth)	458,7mm
C (Height)	1.714,5mm
Unit Weight	110kg
Tank Dimensions/Weight	Integrated
Unit Details	
Max FPS Capacity	12.302 liters
Nitrogen Purity	98% +
Mount	Floor
Electrical	220 VAC / 3 Amp / 50Hz / 1 Phase
Maintenance	Annual or 1,000 Hours ¹
Warranty	One Year ²



1. Whichever comes first per STS terms and conditions.
 2. Extended warranty options available.

OPTIONAL EQUIPMENT

Part Number	Product Description
B20-A-002X	BlastOff III - Early Warning System
A02-MO2-4C	BlastOff IV - Onboard Purity Alarm
A02-QCP	Quick-Check [®] Portable N ₂ Purity Sensor
A02-QCF (PST or 6PST)	N ₂ Blast AutoPurge System 1 or 6 Zone Timer
A02-QCF-PS (1PM, 6PM, 10PM, or 20PM)	Quick-Check Single or Multi-Zone Purity Manifold
PM Box-004	Preventative Maintenance Box (2 years of Annual Filter Kits)